PORCELAIN STEEL PANEL

Whiteboard Resurfacing Material








- PORCELAIN STEEL
 TECHNICAL INFORMATION
- A precisely balanced porcelain enamel ground coat is furnace-fused to both sides of 28 gauge (standard) or 24 gauge (custom) steel.
- The first furnace fuses a ground coat of enamel that is heat-softened at approximately 1450° F. The second furnace firing fuses a coat of enamel to the ground coat enamel

 The first furnace fuses a coat of enamel to the ground coat enamel.
- Color Fusion ceramic top coat is applied providing the desired surface color. Offwhite is standard.
- A fade resistant waterproof resin glue bond the porcelain to a moisture-resistant core and .005" polyester foil backer sheet. Also available with upgraded sheet aluminum
- Renew or replace any torn or worn board with high end porcelain steel whiteboard panels. Magnetic
 porcelain steel dry erase surface is engineered for superior color contrast with dry erase markers.
- Standard gloss porcelain provides superior writability and erasability with no ghosting. Reduced surface light distortion enhances visibility to provide optimum eye comfort.
- Porcelain steel layer is permanently laminated to durable and moisture-resistant substrate, retaining rigidity
 while staying easy to handle. Available in ¼" or ½" thick panels.
- Panel roller and adhesive available to ensure easy installation.
- Limited lifetime warranty. SCS Indoor Advantage Gold Certified.

PART NO.	ITEM	DIMENSIONS	SHIP WT.
1/4" PANELS			
2H2XD	Porcelain Steel Panel - ¼ in.	4'H × 4'W	48 lbs
2H2XG	Porcelain Steel Panel - ¼ in.	4'H × 6'W	72 lbs
2H2XH	Porcelain Steel Panel - ¼ in.	4'H × 8'W	96 lbs
½" PANELS			
202XD	Porcelain Steel Panel - 1/2 in.	$4'H \times 4'W$	72 lbs
202XG	Porcelain Steel Panel - ½ in.	4'H × 6'W	108 lbs
202XH	Porcelain Steel Panel - ½ in.	4'H × 8'W	144 lbs

Shipping weights are listed on a per item basis and may vary based on quantities ordered.





^{**}Ships UPS with large package surcharge or additional handling fee.